INOV8™
Customer Inspired Innovation

EXS Oil in Water Analyser

Intelligent Control - Side Stream Analyser

Customer inspired innovation

Leveraging decades of innovation experience for the Oil & Gas industry, Inov8™ Systems introduce the next generation of products for an evolving market with dynamic demands.

Features

- New **RapidWave**™ ultrasonic self cleaning
- Low power DC voltage requirements - other options including AC available
- Multiple Communication options for Management Capabilities
- Small footprint only requiring front access for easy maintenance and installation
- Large user configurable colour display
- Less than 25KG weight
- 316SS Exd Hazardous ATEX, IECEx and C1D1 Certification

Benefits

- Low cost of ownership with no regular maintenance, no routine calibration and no added chemicals
- Simple to use interface for set-up and control
- Wall, rack or stand mounting options
- Minimal installation requirements (24VDC, Exd)
- Remote Monitoring and Automatic Process Control
- Continuous real-time measurements; <1 sec response time to process changes
- 24 month standard warranty

INOV8™
Customer Inspired Innovation

Technical Specifications

OPERATING CONDITIONS:

Ambient Temperature	Ambient Temperature -20C to 60C
Process Temperature	-20C to135C (200C on request)
Design Pressure	35barg (higher options available)
Standard Operating Pressure	0 - 10barg (higher options available)
Flow Velocity	0.5 – 10 m/s

MECHANICAL:

Dimensions	W268mm x H353mm x D177mm
Weight	<25KG
Process Connections	3/4" NPT
Wetted Parts	316L SS Standard (others available)
Non-Wetted Parts	316L SS
Enclosure	IP66 / IPW 66

MEASUREMENT:

Light Source	Solid State CW 5mW Laser or Deep UV LED
Measurement Method	Fluorescence Spectrometry[2]
Range	PPB - 10,000 ppm*
Range (Deep UV)	PPB > 10,000ppm*
Accuracy	+/- 1%
Sample Rate	< 1 sec
Repeatability	< +/- 1%

CONTROLLER INTERFACE:

Analogue	4-20mA, HART, Modbus TCP/IP
Ethernet	10 Mbps
Wifi	
Digital	2 x Volt free contacts

* Under controlled conditions and dependent on API of oil

ELECTRICAL:

Standard Power Voltage/Current	24VDC / 6A (230/110 VAC 50/60Hz option available)
Power Consumption	DC 20W nominal, 140W peak. AC 15W nominal, 84W peak
Cable Entries	2 entries - M20x1.5mm

COMPLIANCE:

Directives:

- 2014/68/EU Pressure Equipment Directive, module A1
- 2014/34/EU ATEX Directive Exd IIG Class 1 Division 1, Zone 1

Standards:

FM3600	Electric Equipment for use in Hazardous Locations General requirements
FM3615	Explosion Proof Electrical Equipment General Requirements
FM3810	Electrical Equipment For Measurement, Control and Laboratory Use
ANSI/IEC 60529	Degrees of Protection Provided By Enclosures (IP code)
CSA-C22.2 No. 30	Explosion Proof Enclosures For Use In Class 1 Hazardous Locations.
CSA-C22.2 No. 142	Process Control Equipment
CSA-C22.2 No. 60529	Degrees of Protection Provided By Enclosures
IECEx EN 60079-0	Explosive atmospheres Part 0: Equipment General Requirements
IECEx EN 60079-1	Explosive atmospheres Part 1: Equipment protected by flameproof enclosures "d"
IMO107(49)	Marine 15 ppm regulations
DNVGL-CP-0485	Clean Design 5 ppm regulations

Patent number 2580699 (UK)
Patent number 2600454 (UK)
Patent number 2614934 (UK)
Patent Number 3127511 (CA)
Patent Number 11994461 (US)
Patent number 3914898 (EU)
Patent Number 2798310 (RU)
EU and UK design registration: 005822616-0002